

DATA: 20/09/2022

72S45141006: 4SDPM 6/14C

DATI POMPA E MOTORE




n (rpm):	2900	Fasi motore:	1~
H max (m):	77.00	Un (V):	230
H min (m):	28.00	fn (Hz):	50
Q min (mc/h):	3.00	Poli:	2
Q max (mc/h):	8.40	Max temperatura del liquido (°C):	35
Pn (kW):	1.50	P1 (kW):	2.33 kW
Pn (HP):	2.00	Peso (kg):	18.100
Tipo motore:	IM		

MATERIALI

Camicia esterna:	Acciaio inossidabile al Cr-Ni 1.4301 EN 10088 (AISI 304)	Diffusore:	Null
Corpo di mandata:	Acciaio inossidabile al Cr-Ni 1.4301 EN 10088 (AISI 304)	Albero:	Acciaio inossidabile al Cr-Ni 1.4301 EN 10088 (AISI 304)
Lanterna aspirante:	Acciaio inossidabile al Cr-Ni 1.4301 EN 10088 (AISI 304)	Filtro:	Acciaio inossidabile al Cr-Ni 1.4301 EN 10088 (AISI 304)
Corpo stadio:	Acciaio inossidabile al Cr-Ni 1.4301 EN 10088 (AISI 304)	Viti:	Acciaio inossidabile al Cr-Ni 1.4301 EN 10088 (AISI 304)
Girante:	Noryl PPO-GF20		

DATA: 20/09/2022

72S45141006: 4SDPM 6/14C



DATA: 20/09/2022

72S45141006: 4SDPM 6/14C

DIMENSIONI (MM)

dn2: Rp 2"
f: 607.00 mm
fM: 1054.00 mm
I5: 98

